according to UK REACH Regulation

Revision	date:	23.01	2024
11011011	uulo.	20.01	.2027

FuturaGen Com4 Flüssigkeit Product code: 750961,750962

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

FuturaGen Com4 Flüssigkeit

Product group:

UFI:

Liquid component 2FS2-95M7-720E-DS7X

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Manufacture of dental products.

### 1.3. Details of the supplier of the safety data sheet

Company name:	Schütz Dental GmbH	
Street:	Dieselstrasse 5-6	
Place:	D-61191 Rosbach v.d.H	
Telephone:	+49 (0) 6003 - 814-0	Telefax: +49 (0) 6003 - 814-906
e-mail:	info@schuetz-dental.de	
Internet:	www.schuetz-dental.de	
Responsible Department:	+49 (0) 6003 - 814-630	
1.4. Emergency telephone	+49 (0) 6131 - 19240	
<u>number:</u>	Poison Information Centre, University Mainz (24	1 h)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

#### **GB CLP Regulation**

### Hazard components for labelling

Methyl methacrylate

1,4-Butandiol dimethacrylate Danger

Signal word:

#### **Pictograms:**



#### Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

#### **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing

### according to UK REACH Regulation

FuturaGen Com4 Flüssigkeit								
Revision date: 23.01.2024	Product code: 750961,750962	Page 2 of 10						
	protection.							
P302+P352	IF ON SKIN: Wash with plenty of Water and soap.							
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.							
P362+P364	Take off contaminated clothing and wash it before reuse.							
P370+P378	In case of fire: Use Foam, Extinguishing powder, Carbon dioxide (CO2) to extinguish.							
P403+P235	Store in a well-ventilated place. Keep cool.							
P501	Dispose of contents/container to as hazardous waste - in accordance with local and national legislation - suitable, approved incinerator for combustible organic waste.							

### 2.3. Other hazards

No information available.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixture based on methyl methacrylate.

#### Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
80-62-6	Methyl methacrylate			
	201-297-1		01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens	. 1, STOT SE 3; H225 H315 H317 H	335	
2082-81-7	1,4-Butandiol dimethacrylate			5 - < 10 %
	218-218-1		01-2119967415-30	
	Skin Sens. 1; H317			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE CAS No EC No Chemical name Quantity Specific Conc. Limits, M-factors and ATE 201-297-1 80-62-6 Methyl methacrylate 90 - < 95 % inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg 2082-81-7 218-218-1 1,4-Butandiol dimethacrylate 5 - < 10 % dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg

### SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **General information**

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

according to UK REACH Regulation

### FuturaGen Com4 Flüssigkeit

Revision date: 23.01.2024

Product code: 750961,750962

Page 3 of 10

#### After ingestion

Do NOT induce vomiting. Rinse mouth. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder

#### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators. Vapours can form explosive mixtures with air.

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Schutzhandschuhe und Augen- / Gesichtsschutz tragen. Einatmen von Dampf vermeiden. Siehe Abschnitt: 8.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

## 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

When using do not eat, drink, smoke, sniff. Use only in well-ventilated areas. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

### according to UK REACH Regulation

### FuturaGen Com4 Flüssigkeit

Revision date: 23.01.2024

Product code: 750961,750962

Page 4 of 10

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Caution! Transport usually takes place at temperatures above the flash point.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Protect from direct sunlight.

### Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

#### Further information on storage conditions

Keep away from heat.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

#### **DNEL/DMEL** values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
80-62-6	Methyl methacrylate						
Worker DNEL,	long-term	inhalation		208 mg/m <sup>3</sup>			
Worker DNEL, long-term dermal 17 mg/kg bw/day							

#### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear eye/face protection.

#### Hand protection

Wear suitable protective gloves. To protect against splashes: butyl; EN 374. To protect against immersion: butyl; 0.7 mm or thicker, EN 374. The suitability of gloves should be agreed with the manufacturer. Change gloves in the event of contamination or if the breakthrough time is exceeded. Resistance of the glove material: see information from the glove manufacturer.

#### Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

#### **Respiratory protection**

Wear suitable respiratory protection if technical measures are inadequate or not available and exposure is to be expected that exceeds the DNEL (derived exposure level below which the substance does not cause any harm to human health). A suitable breathing mask with filter type A (EN141 or EN405) is recommended. A self-contained breathing apparatus may be necessary if particularly high vapor concentrations are formed.

### according to UK REACH Regulation

## FuturaGen Com4 Flüssigkeit

Revision date: 23.01.2024

Product code: 750961,750962

Page 5 of 10

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and		
Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Melting point/freezing point:		-48 °C
Boiling point or initial boiling point and	d	100,5 °C
boiling range:		
Flammability:		not applicable
Lauran ann la sian linsitas		not applicable
Lower explosion limits:		2,1 vol. %
Upper explosion limits:		12,5 vol. %
Flash point:		10 °C
Auto-ignition temperature:		421 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Water solubility:		12,5 g/L
(at 20 °C)		
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		1,38
Vapour pressure:		36 hPa
(at 20 °C)		
Density (at 15,5 °C):		0,949 g/cm <sup>3</sup>
Relative vapour density:		3,5
(at 20 °C)		
9.2. Other information		
Information with regard to physical	hazard classes	
Self-ignition temperature		
Solid:		not applicable
Gas:		not applicable
Oxidizing properties		
Not oxidising.		
Other safety characteristics		
Evaporation rate:		not determined
Solid content:		not determined
Viscosity / dynamic:		0,53 mPa·s
(at 20 °C)		

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Highly flammable, Vapours can form explosive mixtures with air.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators. Protect from direct sunlight.

### according to UK REACH Regulation

## FuturaGen Com4 Flüssigkeit

Revision date: 23.01.2024

Product code: 750961,750962

Page 6 of 10

### 10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix tested

	Dose	Species	Source
LD50, oral	7870 mg/kg	Rat	
LD50, dermal	> 5000 mg/kg	Rabbit	
LC50, inhalation (vapour) (4 h)	78 mg/l	Rat	

## CAS No Chemical name

CAS NO	Chemical name						
	Exposure route	Dose		Species	Source	Method	
80-62-6	Methyl methacrylate				_	-	
	oral	LD50 mg/kg	>5000	Rat	OECD 401		
	dermal	LD50 mg/kg	>5000	Rabbit			
	inhalation vapour	LC50	29,8 mg/l	Rat			
2082-81-7	1,4-Butandiol dimethacry	ate					
	oral	LD50 mg/kg	> 10000	Rat			
	dermal	LD50 mg/kg	> 3000	Rabbit			

### Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (Methyl methacrylate; 1,4-Butandiol dimethacrylate)

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. (Methyl methacrylate)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Acute (short-term) fish toxicity

### according to UK REACH Regulation

### FuturaGen Com4 Flüssigkeit

Revision date: 23.01.2024

Product code: 750961,750962

Page 7 of 10

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method			
80-62-6	Methyl methacrylate	Methyl methacrylate								
	Acute fish toxicity	LC50 mg/l	> 79		Oncorhynchus mykiss (Rainbow trout)	OECD 203				
	Acute algae toxicity	ErC50 mg/l	> 110		Selenastrum capricornutum	OECD 201				
	Acute crustacea toxicity	EC50	69 mg/l		Daphnia magna (Big water flea)	OECD 202				
	Crustacea toxicity	NOEC	37 mg/l		Daphnia magna (Big water flea)	OECD 202				
2082-81-7	1,4-Butandiol dimethacryl	ate								
	Acute fish toxicity	LC50 mg/l	32,5		Oncorhynchus mykiss (Rainbow trout)					
	Acute crustacea toxicity	EC50 mg/l	7,51		Daphnia magna (Big water flea)	OECD 211				
	Crustacea toxicity	NOEC mg/l	7,51		Selenastrum capricornutum					

#### 12.2. Persistence and degradability

Biodegradable.

#### 12.3. Bioaccumulative potential

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
2082-81-7	1,4-Butandiol dimethacrylate	3,1

#### 12.4. Mobility in soil

Mobility in soil: No adsoption in soil or sediment.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### Further information

Avoid release to the environment.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

according to UK REACH Regulation

## FuturaGen Com4 Flüssigkeit

Revision date: 23.01.2024

Product code: 750961,750962

Page 8 of 10

# **SECTION 14: Transport information**

Land transport (ADR/RID)		
14.1. UN number or ID number:	UN 1247	
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
Classification code:	F1	
Limited quantity:	1 L	
Excepted quantity:	E2	
Transport category:	2	
Hazard No:	339	
Tunnel restriction code:	D/E	
Other applicable information (land trans	port)	
SAPT: > 60 °C		
Inland waterways transport (ADN)		
<u>14.1. UN number or ID number:</u>	UN 1247	
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
Classification code:	F1	
Limited quantity:	1 L	
Excepted quantity:	E2	
Other applicable information (inland wat SAPT: > 60 °C	erways transport)	
Marine transport (IMDG)		
14.1. UN number or ID number:	UN 1247	
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED	
<u>14.3. Transport hazard class(es):</u>	3	
14.4. Packing group:	II	
Hazard label:	3	
Special Provisions:	-	
Limited quantity:	1L	
Excepted quantity:	E2	
EmS:	F-E, S-D	
Other applicable information (marine tra SAPT: > 60 °C	insport)	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	UN 1247	
14.2. UN proper shipping name:		
	METHYL METHACRYLATE MONOMER, STABILIZED	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	3 II	
<b>14.4. Packing group:</b> Hazard label:	3    3	
14.4. Packing group: Hazard label: Limited quantity Passenger:	3 II 3 1 L	
<b>14.4. Packing group:</b> Hazard label: Limited quantity Passenger: Passenger LQ:	3 II 3 1 L Y-341	
<b>14.4. Packing group:</b> Hazard label: Limited quantity Passenger: Passenger LQ: Excepted quantity:	3 II 3 1 L Y-341 E2	
<b>14.4. Packing group:</b> Hazard label: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger:	3 II 3 1 L Y-341 E2 353	
<b>14.4. Packing group:</b> Hazard label: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	3 II 3 1 L Y-341 E2 353 5 L	
<b>14.4. Packing group:</b> Hazard label: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger:	3 II 3 1 L Y-341 E2 353	

### according to UK REACH Regulation

FuturaGen Com4 Flüssigkeit		
Revision date: 23.01.2024	Product code: 750961,750962	Page 9 of 10
Other applicable information (air transports SAPT: > 60 °C	rt)	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	Νο	
<b>14.6. Special precautions for user</b> Warning: Combustible liquids.		
14.7. Maritime transport in bulk according to	IMO instruments	
not applicable		
SECTION 15: Regulatory information		
	ations/legislation specific for the substance or mixture	
EU regulatory information	ations/legislation specific for the substance or mixture	
<b>EU regulatory information</b> Restrictions on use (REACH, annex XVII):	ations/legislation specific for the substance or mixture	
<b>EU regulatory information</b> Restrictions on use (REACH, annex XVII): Entry 3, Entry 40		
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40 2010/75/EU (VOC):	90 % (854,1 g/l)	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40 2010/75/EU (VOC): 2004/42/EC (VOC):	90 % (854,1 g/l) 90 % (854,1 g/l)	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40 2010/75/EU (VOC):	90 % (854,1 g/l)	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40 2010/75/EU (VOC): 2004/42/EC (VOC): Information according to 2012/18/EU	90 % (854,1 g/l) 90 % (854,1 g/l)	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40 2010/75/EU (VOC): 2004/42/EC (VOC): Information according to 2012/18/EU (SEVESO III):	90 % (854,1 g/l) 90 % (854,1 g/l)	
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40 2010/75/EU (VOC): 2004/42/EC (VOC): Information according to 2012/18/EU (SEVESO III): National regulatory information	90 % (854,1 g/l) 90 % (854,1 g/l) P5c FLAMMABLE LIQUIDS Observe restrictions to employment for juveniles according to the 'juven work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or	

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

#### Relevant H and EUH statements (number and full text)

Highly flammable liquid and vapour.

H225

### according to UK REACH Regulation

### FuturaGen Com4 Flüssigkeit

Product code: 750961,750962	Page 10 of 10
	Product code: 750961,750962

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)