

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023


Version: 4 (replaces version 3)

Revision: 06.01.2023


SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Sebond Smart Zirkon-Bonder
- **Article number:** 640068
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Dental bonding material
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Schütz Dental GmbH, Dieselstrasse 5-6, D-61191 Rosbach v.d.H. (Germany)
Tel.: +49 (0)6003/814-0 Fax: +49 (0)6003/814-906
www.schuetz-dental.de; e-mail: info@schuetz-dental.de
- **Further information obtainable from:** Tel.: +49 (0)6003/814-630
- **1.4 Emergency telephone number:**
+49 (0) 6003 8140 Schütz Dental (8:00 - 17:00 Uhr) or
+49 (0) 6131 19240 Poison Information Center, University Mainz (24 h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
 - **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
 - **Hazard pictograms**
- 

GHS02



GHS07
- **Signal word** Danger
 - **Hazard-determining components of labelling:**
methyl methacrylate
 - **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
 - **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
 - **2.3 Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version: 4 (replaces version 3)

Revision: 06.01.2023

Trade name: **Sebond Smart Zirkon-Bonder**

(Contd. of page 1)

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 80-62-6	methyl methacrylate	75-100%
EINECS: 201-297-1	⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**· **General information** Immediately remove any clothing soiled by the product.· **After inhalation** Supply fresh air; consult doctor in case of complaints.· **After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**· **Suitable extinguishing agents**

Foam

Fire-extinguishing powder

Carbon dioxide

· **For safety reasons unsuitable extinguishing agents** Water with full jet.· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.· **5.3 Advice for firefighters**· **Protective equipment:** Wear self-contained respiratory protective device.· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version: 4 (replaces version 3)

Revision: 06.01.2023

Trade name: Sebond Smart Zirkon-Bonder

(Contd. of page 2)

- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep receptacles tightly sealed.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Storage between 10 °C and 25 °C.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate	
WEL	Short-term value: 416 mg/m ³ , 100 ppm
	Long-term value: 208 mg/m ³ , 50 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- **Respiratory protection:**
- Not necessary if room is well-ventilated.
- Use suitable respiratory protective device when high concentrations are present.
- Short term filter device:
- Filter A
- **Hand protection** Solvent resistant gloves
- **Material of gloves**
- Butyl rubber, BR
- Nitrile rubber, NBR
- **Penetration time of glove material**
- 0,3 mm
- Penetration time 60 min.
- 0,11 mm
- Penetration time 10 min.
- **Eye/face protection** Safety glasses
- **Body protection:**
- Solvent resistant protective clothing

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version: 4 (replaces version 3)

Revision: 06.01.2023

Trade name: *Sebond Smart Zirkon-Bonder*

(Contd. of page 3)

(Only when handling large quantities)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	<i>Fluid</i>
· Colour:	<i>Colourless</i>
· Odour:	<i>Characteristic</i>
· Odour threshold:	<i>Not determined.</i>
· Melting point/freezing point:	<i>-48 °C</i>
· Boiling point or initial boiling point and boiling range	<i>101 °C</i>
· Flammability	<i>Highly flammable.</i>
· Lower and upper explosion limit	
· Lower:	<i>2.1 Vol %</i>
· Upper:	<i>12.5 Vol %</i>
· Flash point:	<i>10 °C</i>
· Ignition temperature:	<i>430 °C</i>
· Decomposition temperature:	<i>Not determined.</i>
· pH	<i>Not determined</i>
· Viscosity:	
· Kinematic viscosity	<i>Not determined</i>
· dynamic:	<i>Not determined</i>
· Solubility	
· Water at 20 °C:	<i>1.6 g/l</i>
· Partition coefficient n-octanol/water (log value)	<i>Not determined.</i>
· Vapour pressure at 20 °C:	<i>47 hPa</i>
· Density and/or relative density	
· Density at 20 °C:	<i>0.94 g/cm³</i>
· Relative density	<i>Not determined.</i>
· Vapour density	<i>Not determined.</i>

· 9.2 Other information

· Appearance:	
· Form:	<i>Fluid</i>
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	<i>Product is not selfigniting.</i>
· Explosive properties:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
· Solvent content:	
· Organic solvents:	<i>0.0 %</i>
· Molecular weight	<i>100 g/mol</i>
· Change in condition	
· Evaporation rate	<i>Not determined.</i>

· Information with regard to physical hazard classes

· Explosives	<i>Void</i>
· Flammable gases	<i>Void</i>
· Aerosols	<i>Void</i>
· Oxidising gases	<i>Void</i>
· Gases under pressure	<i>Void</i>
· Flammable liquids	<i>Highly flammable liquid and vapour.</i>
· Flammable solids	<i>Void</i>
· Self-reactive substances and mixtures	<i>Void</i>
· Pyrophoric liquids	<i>Void</i>
· Pyrophoric solids	<i>Void</i>

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version: 4 (replaces version 3)

Revision: 06.01.2023

Trade name: *Sebond Smart Zirkon-Bonder*

(Contd. of page 4)

- | | |
|--|-------------|
| · Self-heating substances and mixtures | <i>Void</i> |
| · Substances and mixtures, which emit flammable gases in contact with water | <i>Void</i> |
| · Oxidising liquids | <i>Void</i> |
| · Oxidising solids | <i>Void</i> |
| · Organic peroxides | <i>Void</i> |
| · Corrosive to metals | <i>Void</i> |
| · Desensitised explosives | <i>Void</i> |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with peroxides and other radical forming substances
Danger of polymerization
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
In presence of radical formers (e. g. peroxides), deoxidizing substances, and/or heavy metal ions, polymerization with heat release is possible.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
methyl methacrylate LD-50 oral >5000 mg/kg rat (lit.)
LD-50 inhalativ 7093 ppm/4h rat (lit.)
- **Skin corrosion/irritation** Causes skin irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause respiratory irritation.
- **11.2 Information on other hazards**

- | |
|--|
| · Endocrine disrupting properties |
| None of the ingredients is listed. |

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Type of test Effective concentration Method Assessment**
Toxicity to fish: LC-50: >79 mg/l OECD 203
(MMA) NOEC: 40 mg/l ISO 7346
Time: 96 h EEC84
Species:
Oncorhynchus mykiss

Toxicity to Micro- ECO: 100 mg/l starting inhibition
Organisms Species: of cell growth
(MMA) *Pseudomonas putida*
- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version: 4 (replaces version 3)

Revision: 06.01.2023

Trade name: Sebond Smart Zirkon-Bonder


(Contd. of page 5)

- **Behaviour in environmental systems:**
- **Components:**
 methyl methacrylate Biodegradability: 30,7 %
 Time: 28 d
 Method: OECD 301 C
 Valuation: difficult to decompose
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
 The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must be specially treated adhering to official regulations.
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
 Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
 Packagings that may not be cleansed are to be disposed of in the same manner as the product.
- **Recommended cleansing agents:** Alcohol

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1247
- **14.2 UN proper shipping name**
- **ADR** 1247 METHYL METHACRYLATE MONOMER, STABILIZED solution
- **IMDG, IATA** METHYL METHACRYLATE MONOMER, STABILIZED solution
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 3 (F1) Flammable liquids.

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31


Printing date 06.01.2023

Version: 4 (replaces version 3)

Revision: 06.01.2023

Trade name: *Sebond Smart Zirkon-Bonder*

(Contd. of page 6)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category · Stowage Code	Warning: Flammable liquids. 339 F-E,S-D B SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **National regulations**
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Version: 4 (replaces version 3)

Revision: 06.01.2023

Trade name: Sebond Smart Zirkon-Bonder

(Contd. of page 7)

· **Technical instructions (air):**

Class	Share in %
NK	75-100

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.*
- H315 Causes skin irritation.*
- H317 May cause an allergic skin reaction.*
- H335 May cause respiratory irritation.*

· **Department issuing SDS:** Schütz Dental GmbH

· **Contact:** Dr. U. Krichbaum

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*
- ICAO: International Civil Aviation Organisation*
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)*
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: International Maritime Code for Dangerous Goods*
- IATA: International Air Transport Association*
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: European Inventory of Existing Commercial Chemical Substances*
- ELINCS: European List of Notified Chemical Substances*
- CAS: Chemical Abstracts Service (division of the American Chemical Society)*
- LC50: Lethal concentration, 50 percent*
- LD50: Lethal dose, 50 percent*
- PBT: Persistent, Bioaccumulative and Toxic*
- vPvB: very Persistent and very Bioaccumulative*
- Flam. Liq. 2: Flammable liquids – Category 2*
- Skin Irrit. 2: Skin corrosion/irritation – Category 2*
- Skin Sens. 1: Skin sensitisation – Category 1*
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

· *** Data compared to the previous version altered.**