

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Dialog Bonding Fluid
- **Article number:** 643922
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Dental bonding material
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Schütz Dental GmbH, Dieselstrasse 5-6, D-61191 Rosbach v.d.H. (Germany)
Tel.: +49 (0)6003/814-0 Fax: +49 (0)6003/814-900
www.schuetz-dental.de; e-mail: info@schuetz-dental.de
- **Further information obtainable from:** F&E, Tel.: +49 (0)6003/814-0
- **1.4 Emergency telephone number:**
+49 (0) 6003 8140 Schütz Dental (8:00 - 17:00 Uhr) or
+49 (0) 6131 19240 Poison Information Center, University Mainz (24 h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2	H225 Highly flammable liquid and vapour.
Skin Irrit. 2	H315 Causes skin irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
methyl methacrylate
di-urethane dimethacrylate
diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405 Store locked up.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

Trade name: Dialog Bonding Fluid

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-75%
CAS: 41137-60-4	di-urethane dimethacrylate ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1B, H317	25-50%
CAS: 75980-60-8 EINECS: 278-355-8	diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide ⚠ Repr. 2, H361f; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1B, H317	<2.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **General information** Immediately remove any clothing soiled by the product.
- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents

Fire-extinguishing powder

Foam

Carbon dioxide

Water spray

· **For safety reasons unsuitable extinguishing agents** Water with full jet.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

5.3 Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

Trade name: Dialog Bonding Fluid

(Contd. of page 2)

*Wear protective clothing.**Wear protective equipment. Keep unprotected persons away.**Keep away from ignition sources*· **6.2 Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*· **6.3 Methods and material for containment and cleaning up:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Ensure adequate ventilation.**Do not flush with water or aqueous cleansing agents*· **6.4 Reference to other sections***See Section 7 for information on safe handling**See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.*

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling***Keep receptacles tightly sealed.**Ensure good ventilation/exhaustion at the workplace.*· **Information about fire - and explosion protection:***Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.*· **7.2 Conditions for safe storage, including any incompatibilities**· **Storage**· **Requirements to be met by storerooms and receptacles:***Close container immediately after use and protect product from light incidence.**Storage between 10 °C and 25 °C.*· **Information about storage in one common storage facility:** *Not required.*· **Further information about storage conditions:***Keep receptacle tightly sealed.**Store in cool, dry conditions in well sealed receptacles.*· **7.3 Specific end use(s)** *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****80-62-6 methyl methacrylate**WEL Short-term value: 416 mg/m³, 100 ppmLong-term value: 208 mg/m³, 50 ppm· **Additional information:** *The lists valid during the making were used as basis.*· **8.2 Exposure controls**· **Appropriate engineering controls** *No further data; see item 7.*· **Individual protection measures, such as personal protective equipment**· **General protective and hygienic measures***Keep away from foodstuffs, beverages and feed.**Immediately remove all soiled and contaminated clothing**Wash hands before breaks and at the end of work.**Avoid contact with the eyes and skin.*· **Respiratory protection:** *Not necessary if room is well-ventilated.*· **Hand protection** *Protective gloves.*· **Material of gloves***Butyl rubber, BR**Nitrile rubber, NBR*

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

Trade name: Dialog Bonding Fluid

(Contd. of page 3)

- **Penetration time of glove material**
0,3 mm
Penetration time 60 min.
0,11 mm
Penetration time 10 min.
- **Eye/face protection** Safety glasses

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

- | | |
|---|-----------------|
| · Physical state | Fluid |
| · Colour: | Clear |
| · Odour: | Ester-like |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | -48 °C |
| · Boiling point or initial boiling point and boiling range | 101 °C |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 2.1 Vol % |
| · Upper: | 12.5 Vol % |
| · Flash point: | 10 °C |
| · Ignition temperature: | 430 °C |
| · Decomposition temperature: | Not determined. |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity | Not determined |
| · dynamic: | Not determined |
| · Solubility | |
| · Water: | Not determined |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C: | 47 hPa |
| · Density and/or relative density | |
| · Density: | Not determined |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

· 9.2 Other information

- | | |
|--|---|
| · Appearance: | |
| · Form: | Fluid |
| · Important information on protection of health and environment, and on safety. | |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Change in condition | |
| · Evaporation rate | Not determined. |

· Information with regard to physical hazard classes

- | | |
|--|-------------------------------------|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Highly flammable liquid and vapour. |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

Trade name: Dialog Bonding Fluid

(Contd. of page 4)

· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Exothermic polymerization
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
In presence of radical formers (e. g. peroxides), deoxidizing substances, and/or heavy metal ions, polymerization with heat release is possible.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**
methyl methacrylate LD-50 oral >5000 mg/kg rat (lit.)
 LD-50 inhalativ 7093 ppm/4h rat (lit.)
- **Skin corrosion/irritation** Causes skin irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure**
May cause respiratory irritation.
May cause respiratory irritation.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**
- None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Type of test Effective concentration Method Assessment**
Toxicity to fish: LC-50: >79 mg/l OECD 203
 (MMA) NOEC: 40 mg/l ISO 7346
 Time: 96 h EEC84
 Species:
 Oncorhynchus mykiss

Toxicity to Micro- ECO: 100 mg/l starting inhibition
 Organisms Species: of cell growth
 (MMA) *Pseudomonas putida*
- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

Trade name: Dialog Bonding Fluid


(Contd. of page 5)

- **Behaviour in environmental systems:**
- **Components:**
 - methyl methacrylate Biodegradability: 30,7 %
 - Time: 28 d
 - Method: OECD 301 C
 - Valuation: difficult to decompose
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Also poisonous for fish and plankton in water bodies.
 - Toxic for aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 - Must be specially treated adhering to official regulations.
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA | UN1247 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1247 METHYL METHACRYLATE MONOMER,
STABILIZED, ENVIRONMENTALLY HAZARDOUS
METHYL METHACRYLATE MONOMER, STABILIZED,
MARINE POLLUTANT
METHYL METHACRYLATE MONOMER, STABILIZED |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR | |
|  | |
| <ul style="list-style-type: none"> · Class | 3 (F1) Flammable liquids. |

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

Trade name: Dialog Bonding Fluid

(Contd. of page 6)

· **Label** 3· **IMDG**· **Class** 3 Flammable liquids.· **Label** 3· **IATA**· **Class** 3 Flammable liquids.· **Label** 3· **14.4 Packing group**· **ADR, IMDG, IATA** II· **14.5 Environmental hazards:**Product contains environmentally hazardous substances:
di-urethane dimethacrylate· **Marine pollutant:**No
Symbol (fish and tree)· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

33

· **EMS Number:**

F-E,S-D

· **Stowage Category**

C

· **Stowage Code**SW1 Protected from sources of heat.
SW2 Clear of living quarters.· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

D/E

· **IMDG**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**UN 1247 METHYL METHACRYLATE MONOMER,
STABILIZED, 3, II, ENVIRONMENTALLY
HAZARDOUS

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.05.2022

Version: 13 (replaces version 12)

Revision: 04.05.2022

Trade name: Dialog Bonding Fluid

(Contd. of page 7)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

National regulations

Technical instructions (air):

Class	Share in %
II	50-75

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS:

F & E

Schütz Dental GmbH

Contact: Advisory service dep.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.