

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Futura Basic Cold LF Fluid
- **Article number:** 650760
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** self curing resin
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Schütz Dental GmbH, Dieselstrasse 5-6, D-61191 Rosbach v.d.H. (Germany)
Tel.: +49 (0)6003/814-0 Fax: +49 (0)6003/814-900
www.schuetz-dental.de; e-mail: info@schuetz-dental.de
- **Further information obtainable from:** F&E, Tel. +49 (0)6003/814-100
- **1.4 Emergency telephone number:**
+49 (0) 6003 8140 Schütz Dental (8:00 - 17:00 Uhr) or
+49 (0) 6131 19240 Poison Information Center, University Mainz (24 h)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
methyl methacrylate
2-ethylhexyl methacrylate
tetramethylene dimethacrylate
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 1)

P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Labelling of packages where the contents do not exceed 125 ml
- Hazard pictograms



GHS02 GHS07

- Signal word *Danger*
- Hazard-determining components of labelling:
 methyl methacrylate
 2-ethylhexyl methacrylate
 tetramethylene dimethacrylate
- Hazard statements
 H317 May cause an allergic skin reaction.
- Precautionary statements
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P321 Specific treatment (see on this label).
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- Description: Liquid based on methacryl acid ester, containing an activator.

· Dangerous components:

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	75-100%
CAS: 688-84-6 EINECS: 211-708-6	2-ethylhexyl methacrylate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	10-25%
CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate ⚠ Skin Sens. 1B, H317	2.5-10%

- Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- After inhalation
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- After skin contact
 If skin irritation continues, consult a doctor.
 Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 2)

- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
Water haze
Foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents** Water with full jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Avoid eye and skin contact with the substance.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Storage between 10 °C and 25 °C.
- **Information about storage in one common storage facility:** Store away from foodstuffs.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 3)

- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm
 Long-term value: 208 mg/m³, 50 ppm

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.
 Use suitable respiratory protective device when high concentrations are present.
 Filter A

· Protection of hands: Solvent resistant gloves

· Material of gloves

Butyl rubber, BR
 Nitrile rubber, NBR

· Penetration time of glove material

0,3 mm
 Penetration time 60 min.
 0,11 mm
 Penetration time 10 min.

· Eye protection: Safety glasses

· Body protection:

Solvent resistant protective clothing
 (Only when handling large quantities)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Colourless
Odour: Ester-like
Odour threshold: Not determined.

pH-value: Not determined

· Change in condition

Melting point/freezing point: undetermined
Initial boiling point and boiling range: 101 °C

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 4)

· Flash point:	10 °C
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	430 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	2.1 Vol % 12.5 Vol %
· Vapour pressure at 20 °C:	47 hPa
· Density: · Relative density · Vapour density · Evaporation rate	Not determined Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: dynamic: kinematic: · 9.2 Other information	Not determined Not determined No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Exothermic polymerization
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
In presence of radical formers (e. g. peroxides), deoxidizing substances, and/or heavy metal ions, polymerization with heat release is possible.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
methyl methacrylate LD-50 oral >5000 mg/kg rat (lit.)
 LD-50 inhalativ 7093 ppm/4h rat (lit.)
tetramethylene dimethacrylate LD-50 oral > 5000 mg/kg (rat)
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 5)

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
 - **Type of test** **Effective concentration** **Method** **Assessment**
Toxicity to fish: LC-50: >79 mg/l OECD 203
(MMA) NOEC: 40 mg/l ISO 7346
Time: 96 h EEC84
Species:
Oncorhynchus mykiss

Toxicity to Micro- ECO: 100 mg/l starting inhibition
Organisms Species: of cell growth
(MMA) Pseudomonas putida
- **12.2 Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Components:**
methyl methacrylate Biodegradability: 30,7 %
Time: 28 d
Method: OECD 301 C
Valuation: difficult to decompose
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must be specially treated adhering to official regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
- 07 01 04* other organic solvents, washing liquids and mother liquors
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.09.2018



Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 6)

SECTION 14: Transport information

· 14.1 UN-Number	UN1247
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	1247 METHYL METHACRYLATE MONOMER, STABILIZED mixture
· ADR	
· IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED mixture
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 7)

· UN "Model Regulation":

UN 1247 METHYL METHACRYLATE MONOMER,
STABILIZED MIXTURE, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Technical instructions (air):

Class	Share in %
III	2.5-10

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Schütz Dental GmbH

· Contact: Dr. U. Krichbaum

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version: 4

Revision: 10.09.2018

Trade name: Futura Basic Cold LF Fluid

(Contd. of page 8)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**** Data compared to the previous version altered.***

GB