Printing date 06.09.2018 Version: 13 Revision: 06.09.2018

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Futura Press N Flüssigkeit

· Article number: 650261, 650262

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture self curing resin

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Schütz Dental GmbH, Dieselstrasse 5-6, D-61191 Rosbach v.d.H. (Germany)

Tel.: +49 (0)6003/814-0 Fax: +49 (0)6003/814-900 www.schuetz-dental.de; e-mail: info@schuetz-dental.de

· Further information obtainable from: F&E, Tel. +49 (0)6003/814-100

· 1.4 Emergency telephone number:

+49 (0) 6003 8140 Schütz Dental (8:00 - 17:00 Uhr) or

+49 (0) 6131 19240 Poison Information Center, University Mainz (24 h)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate

tetramethylene dimethacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P241 *Use explosion-proof electrical/ventilating/lighting equipment.* 

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)

Version: 13 Printing date 06.09.2018 Revision: 06.09.2018

Trade name: Futura Press N Flüssigkeit

(Contd. of page 1)

- · Labelling of packages where the contents do not exceed 125 ml
- · Hazard pictograms





- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate

tetramethylene dimethacrylate

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Liquid based on methacryl acid ester, containing an activator.

	· Dangerous components:		
Ī			75-100%
	EINECS: 201-297-1	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
ſ		· · · · · · · · · · · · · · · · · · ·	2.5-10%
	EINECS: 218-218-1	🗘 Skin Sens. 1B, H317	

<sup>·</sup> Additional information For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information Immediately remove any clothing soiled by the product.
- · After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact

*Immediately wash with water and soap and rinse thoroughly.* 

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 06.09.2018 Version: 13 Revision: 06.09.2018

Trade name: Futura Press N Flüssigkeit

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Water haze

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

Avoid eye and skin contact with the substance.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Storage between 10 °C and 25 °C.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Printing date 06.09.2018 Version: 13 Revision: 06.09.2018

Trade name: Futura Press N Flüssigkeit

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A

- · Protection of hands: Solvent resistant gloves
- · Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

· Penetration time of glove material

0.3 mm

Penetration time 60 min.

0,11 mm

Penetration time 10 min.

- · Eye protection: Tightly sealed goggles.
- · Body protection:

Solvent resistant protective clothing (Only when handling large quantities)

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
• Odour: Ester-like
• Odour threshold: Not determined.

· pH-value: Not determined

· Change in condition

Melting point/freezing point: -48 °C Initial boiling point and boiling range: 100 °C

· Flash point: 10 °C

· Flammability (solid, gaseous) Not applicable.

(Contd. on page 5)

Printing date 06.09.2018 Version: 13 Revision: 06.09.2018

Trade name: Futura Press N Flüssigkeit

	(Contd. of page 4
· Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapour pressure at 20 °C:	47 hPa
Density at 20 °C:	0.9451 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
dynamic:	Not determined
kinematic:	Not determined
· Solvent content:	
Solids content:	0.0 %
9.2 Other information	No further relevant information available.

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Exothermic polymerization
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

In presence of radical formers (e. g. peroxides), deoxidizing substances, and/or heavy metal ions, polymerization with heat release is possible.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

methyl methacrylate LD-50 oral >5000 mg/kg rat (lit.)

LD-50 inhalativ 7093 ppm/4h rat (lit.)

tetramethylene dimethacrylate LD-50 oral > 5000 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

(Contd. on page 6)

Printing date 06.09.2018 Version: 13 Revision: 06.09.2018

Trade name: Futura Press N Flüssigkeit

(Contd. of page 5)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Type of test Effective concentration Method Assessmen

Toxicity to fish: LC-50: >79 mg/l OECD 203 (MMA) NOEC: 40 mg/l ISO 7346
Time: 96 h EEC84
Species:

Oncorhynchus mykiss

Toxicity to Micro- ECO: 100 mg/l starting inhibition

Organisms Species: of cell growth

(MMA) Pseudomonas putida

- · 12.2 Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Components:

methyl methacrylate Biodegradability: 30,7 %

*Time:* 28 d

Method: OECD 301 C

Valuation: difficult to decompose

- $\cdot \textbf{12.3 Bioaccumulative potential} \ \textit{No further relevant information available}.$
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

07 01 04\* other organic solvents, washing liquids and mother liquors

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GB

*Printing date 06.09.2018 Version: 13 Revision: 06.09.2018* 

Trade name: Futura Press N Flüssigkeit

(Contd. of page 6)

mixture  3 (F1) Flammable liquids.
STABILIZED mixture METHYL METHACRYLATE MONOMER, STABILIZ mixture  3 (F1) Flammable liquids.
METHYL METHACRYLATE MONOMER, STABILIZ. mixture  3 (F1) Flammable liquids.
3
3 Flammable liquids.
3
II
No
Warning: Flammable liquids.
33 E E S D
F-E,S-D B
SW2 Clear of living quarters.
f
Not applicable.
17
1L Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per unter packaging: 50 ml
2
D/E
IL .
Code: E2
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Printing date 06.09.2018 Version: 13 Revision: 06.09.2018

Trade name: Futura Press N Flüssigkeit

(Contd. of page 7)

· UN "Model Regulation":

UN 1247 METHYL METHACRYLATE MONOMER,

STABILIZED MIXTURE, 3, II

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Technical instructions (air):

Class	Share in %
III	2.5-10

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- Department issuing SDS: F & E
- · Contact: Dr. U. Krichbaum
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* \* Data compared to the previous version altered.